

AD-A010 619

THE USE OF SHAPED CAVITIES TO IMPROVE THE
SIDEWALL BOUNDARY LAYER QUALITY IN GAS
DYNAMIC LASERS

James S. Petty, et al

Aerospace Research Laboratories
Wright-Patterson Air Force Base, Ohio

March 1975

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE

ADA010619

ARL TR 75-0024

168101



THE USE OF SHAPED CAVITIES TO IMPROVE THE SIDEWALL BOUNDARY LAYER QUALITY IN GAS DYNAMIC LASERS

JAMES S. PETTY


JAMES R. COOPER, CAPTAIN, USAF

ROBERT H. KORKEGI

THEORETICAL AERODYNAMICS RESEARCH LABORATORY/ARL

MARCH 1976

INTERIM REPORT



Approved for public release; distribution unlimited

NATIONAL TECHNICAL
INFORMATION SERVICE

AEROSPACE RESEARCH LABORATORIES/LH

Building 450 - Area E

Wright-Patterson Air Force Base, Ohio 45433

AIR FORCE SYSTEMS COMMAND
United States Air Force



Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARL 75-0024	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) THE USE OF SHAPED CAVITIES TO IMPROVE THE SIDEWALL BOUNDARY LAYER QUALITY IN GAS DYNAMIC LASERS		5. TYPE OF REPORT & PERIOD COVERED Technical-Interim
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) James S. Petty James R. Cooper, Capt, USAF Robert H. Korkegi		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Theoretical Aerodynamics Research Laboratory (LH) Aerospace Research Laboratories (AFSC) Wright-Patterson AFB, Ohio 45433		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61102F; 7064-06-12
11. CONTROLLING OFFICE NAME AND ADDRESS Aerospace Research Laboratories (ARL) Bldg. 450, Area B Wright-Patterson AFB, Ohio 45433		12. REPORT DATE March 1975
		13. NUMBER OF PAGES 14
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) cavities gas dynamic lasers separated flow		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A series of cavity shapes was tested on the sidewall of a Mach 3 high Reynolds number wind tunnel to determine the effects of the cavity and its downstream lip shape on the external flow. Various mass injection rates into the cavity were provided. Holographic interferometry, oil flow, and a fast response surface pressure transducer were used to take data. Results indicate that a rectangular cavity with a lip shaped as a short rounded overhang least disturbs the turbulent boundary layer. Low levels of mass injection were found to have little effect on boundary layer quality.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

1

PREFACE

This report was prepared by Dr. James S. Petty, Capt James R. Cooper and Dr. Robert H. Korkegi of the Theoretical Aerodynamics Research Laboratories, Air Force Systems Command, United States Air Force, under Project 7064, entitled "High Velocity Fluid Mechanics."

The reported wind tunnel tests were performed in ARL's 3" x 3" Mach number 3 wind tunnel.

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Organizations or individuals receiving reports via Aerospace Research Laboratories automatic mailing lists should refer to the ARL number of the report received when corresponding about change of address or cancellation. Such changes should be directed to the specific laboratory originating the report. Do not return this copy; retain or destroy.

Reports are not stocked by the Aerospace Research Laboratories. Copies may be obtained from:

National Technical Information Services
Clearinghouse
Springfield, VA 22151

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER:

Elizabeth Day
ELIZABETH DAY
Technical Documents
and STINFO Office

ADDITIONAL	
YES	White Section <input type="checkbox"/>
NO	Dark Section <input type="checkbox"/>
NO	<input type="checkbox"/>
STANDARDIZATION COSTS	
YES	NO
YES	NO
A	

This report has been reviewed and cleared for open publication and public release by the appropriate Office of Information in accordance with AFR 190.12 and DODD 5230.0. There is no objection to unlimited distribution of this report to the public at large, or by DDC to the National Technical Information Service.

SECTION I

INTRODUCTION

Cutouts such as the mirror cavity and the one for the interstage duct in gas dynamic lasers such as the SSD (Fig 1) can cause nonuniformity and extensive thickening of the sidewall turbulent boundary layer.

The quality of the sidewall boundary layer is a key factor in the performance of the laser diffuser in which the flow must be recompressed effectively to exhaust to the atmosphere. It is particularly important as the sidewall boundary layer is subjected to three-dimensional shock wave interactions which cause separation and flow deterioration at much lower pressure ratios than for two-dimensional shock wave interactions (ref 1). Thus the sidewall interaction is the limiting factor in diffuser performance.

If the sidewall boundary layer is highly nonuniform and very thick, diffuser performance will be further limited.

It is the purpose of this report to present results of a study of various cavity configurations and to recommend a design which least disturbs the sidewall boundary layer and should therefore help to improve diffuser performance.

SECTION II

CAVITY SHAPE STUDIES

Configurations investigated on the wall of a 3" x 3" Mach number 3 wind tunnel at AKL are a circular cavity (Fig 2a), a rectangular (essentially two-dimensional) cavity (Fig 2b), and four different downstream lip shapes for these cavities, including a square lip (Fig 3a), a lip with a short, circular overhang (Fig 3b), a lip with a long overhang (Fig 3c), and a rounded shoulder (Fig 3d).

Blowing was also investigated in order to simulate the effect of nitrogen injection used to avoid thermal blooming in the interstage duct.

In all cases the cavity length was approximately ten times the thickness of the oncoming turbulent boundary layer. Equivalent Reynolds numbers were of the order of 10^7 .

1. CIRCULAR CAVITY

According to oil flows and interferograms the flow of a turbulent boundary layer across a circular cavity (Fig 2a) is highly nonuniform spanwise (three-dimensional) and results in the thickening of the boundary layer irrespectively of the type of lip used. An oil flow pattern tunnel and cavity wall is given in Fig 4.

2. RECTANGULAR CAVITY

In all cases, the flow over a rectangular cavity extending from wall to wall in the wind tunnel (Fig 2b) was nearly uniform (two-dimensional) as shown in oil flow of Fig 5.

A rectangular cavity with a square lip (Fig 3a) and the rounded shoulder (Fig 3d) both resulted in a strong disturbance including a shock and separation bubble at reattachment, as illustrated in Fig 6a and shown in the interferograms of Fig 7. This configuration produces a thick turbulent boundary layer on the diffuser sidewall, prone to early and extensive separation.

A rectangular cavity with a long, rounded overhang (Fig 3c) resulted in instability and oscillation of the separated boundary layer with expected poor diffuser performance.

The rectangular cavity with a short rounded overhang (Fig 3b) gave the cleanest reattachment with minimal disturbance as illustrated in Fig 6b, and shown in the interferogram of Fig 8. This configuration is expected to least degrade diffuser performance.

3. EFFECT OF BLOWING

Tests were made with air injected nearly uniformly across the floor of the cavity in order to simulate blowing to avoid thermal blooming in the interstage duct. The mass flows injected were varied up to approximately

5% of the boundary layer mass flow across the cavity. For rates up to 1%, the mass injected had little effect on the cavity flow. At a rate of 5%, there is significant degradation as indicated in Fig 9 by the shocks and boundary layer lift off downstream of the cavity. It is expected that rates of 20% will cause the boundary layer to lift off the surface so that the lip shape becomes totally ineffective.

SECTION III

CONCLUSIONS

Of the circular and rectangular cavities with various lip configurations, a rectangular cavity with a lip shaped as a short, rounded overhang least disturbs the turbulent boundary layer and is therefore recommended for consideration for the various sidewall cavities (mirror, interstage duct) in gas dynamic lasers. Blowing rates up to 1% of the boundary layer mass flow show little effect on boundary layer quality.

Although the experiments described are for a turbulent boundary layer and only one Reynolds number, other experiments with laminar boundary layers over cavities show qualitatively the same behavior (ref 2).






Figure 1 GAS DYNAMIC LASER (SSD)




a. Circular



b. Rectangular


Figure 2 CAVITY SHAPES




a. Square



b. Short rounded overhang



c. Long rounded overhang



d. Round shoulder

Figure 3 DOWNSTREAM LIP SHAPES



Figure 4 OIL FLOW PATTERN NEAR CIRCULAR CAVITY






Figure 5 OIL FLOW PATTERN NEAR RECTANGULAR CAVITY



a. Strong disturbance at reattachment
and thick boundary layer



b. Weak or minimal disturbance at
reattachment

Figure 6 TYPES OF DOWNSTREAM CONDITIONS



Square

Rounded

Long Overhang

Short Overhang

Figure 7 INTEROferograms OF FLOW OVER CAVITIES WITH
DIFFERENT REATTACHMENT LIP SHAPES





Figure 8 EFFECT OF MASS INJECTION ON FLOW OVER CAVITY WITH SHORT OVERHANG LIP



0% 5%
Square Lip



0% 5%
Rounded Lip

Figure 9 EFFECT OF MASS INJECTION ON FLOW OVER CAVITIES

REFERENCES

- Ref 1: Korkegi, R. H., "Comparison of Shock-Induced Two- and Three Dimensional Incipient Turbulent Separation" to appear in AIAA Journal.
- Ref 2: Smith, R. R., AF Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio, Private Communications, October 1974.

*Note: A more extensive report on cavity flows will be issued by ARL at a later date.